PassLeader Valid 300-360 Dumps with VCE and PDF (Question 26 - Question 30)

New 300-360 exam questions from PassLeader 300-360 dumps! Welcome to download the newest PassLeader 300-360 VCE and PDF dumps: http://www.passleader.com/300-360.html (185 Q&As --> 208 Q&As --> 230 Q&As --> 262 Q&As)

P.S. Free 300-360 dumps are available on Google Drive shared by PassLeader:

https://drive.google.com/open?id=0B-ob6L QjGLpWVVreDl3bGRhakk

QUESTION 26

Cisco 7925G phones are experiencing intermittent connectivity issues. The wireless survey reveals that the facility has no current coverage holes. The radios on the 2.4GHz channel have all been statically set to power level 1. Which two reasons could explain why the phones are having issues on this wireless network? (Choose two.)

- A. The phones are experiencing excessive co-channel interference.
- B. The phones only operate on the 2.4 GHz band when the power level is above 25 mW.
- C. The phones are not transmitting at the same power levels as the access points.
- D. The phones are experiencing delays of less than 30 ms within their coverage cell.
- E. The phones are receiving greater than -67 dBm RSSI on the 2.4 GHz band.

Answer: AC

QUESTION 27

An engineer would like to calibrate the RF environment to improve accuracy. Which wireless attribute is added to the floor-level calculation by calibrating the floor?

- A. attenuation
- B. TX power
- C. multipath
- D. SNR

Answer: A

OUESTION 28

An engineer is deploying an outdoor Mesh network. Which four major factors should be considered? (Choose four.)

- A. power
- B. buildings
- C. traffic lights
- D. satellite dishes
- E. line of sight
- F. network connectivity
- G. power lines
- H. mounting

Answer: AEFH

OUESTION 29

An engineer is performing a predictive wireless design for a Parts Distribution Center, which requires data and location services. Which three requirements are inputs to the design? (Choose three.)

- access points with directional antennas
- B. continuous -67 dBm coverage from one access point
- C. overlapping -75 dBm coverage from three access points
- D. overlapping -67 dBm coverage from two access points
- E. access points in IPS mode
- F. continuous -72 dBm coverage from one access point
- G. access points in corners and along perimeters

Answer: BCG Explanation:

http://www.cisco.com/c/en/us/td/docs/solutions/Enterprise/Mobility/WiFiLBS-DG/wifich5.html

QUESTION 30

A Cisco 7925 phone at a client's location is not registering with CUCM. The engineer analyzes a packet capture, sees that the phone receives an IP, and downloads the proper configuration file from TFTP successfully. What type of messages should the phone be sending at this point?

- A. H.245
- B. H.323
- C. MCGP
- D. SCCP

Answer: D

New 300-360 exam questions from PassLeader 300-360 dumps! Welcome to download the newest PassLeader 300-360 VCE and PDF dumps: http://www.passleader.com/300-360.html (185 Q&As --> 208 Q&As --> 230 Q&As --> 262 Q&As)
P.S. Free 300-360 dumps are available on Google Drive shared by PassLeader:
https://drive.google.com/open?id=0B-ob6L_QjGLpWVVreDl3bGRhakk