

Premium PassLeader 300-375 Dumps with VCE and PDF Download (Question 26 - Question 30)

New 300-375 exam questions from PassLeader 300-375 dumps! Welcome to download the newest PassLeader 300-375 VCE and PDF dumps: <http://www.passleader.com/300-375.html> (119 Q&As --> 133 Q&As --> 156 Q&As --> 169 Q&As)

P.S. Free 300-375 dumps are available on Google Drive shared by PassLeader:

https://drive.google.com/open?id=0B-ob6L_QjGLpQ2hZQ0c4c2d1QjA

QUESTION 26

An engineer must change the wireless authentication from WPA2-Personal to WPA2- Enterprise. Which three requirements are necessary? (Choose three.)

- A. EAP
- B. 802.1x
- C. RADIUS
- D. per-shared key
- E. 802.11u
- F. fast secure roaming
- G. 802.11i

Answer: ACG

QUESTION 27

Which two considerations must a network engineer have when planning for voice over wireless roaming? (Choose two.)

- A. Roaming with only 802.1x authentication requires full reauthentication.
- B. Full reauthentication introduces gaps in a voice conversation.
- C. Roaming occurs when a phone has seen at least four APs.
- D. Roaming occurs when the phone has reached -80 dBm or below.

Answer: AB

QUESTION 28

Refer to the exhibit. What is the 1.1.1.1 IP address?

- A. the wireless client IP address
- B. the RADIUS server IP address
- C. the controller management IP address
- D. the lightweight IP address
- E. the controller AP-manager IP address
- F. the controller virtual interface IP address

Answer: F

QUESTION 29

An engineer is deploying EAP-TLS as the authentication mechanism for an 802.1X-enabled wireless network. Which network device is responsible for applying the digital signature to a certificate to ensure that the certificate is trusted and valid?

- A. supplicant
- B. CA server
- C. wireless controller
- D. authentication server

Answer: B

QUESTION 30

An engineer is configuring a new mobility anchor for a WLAN on the CLI with the config wlan mobility anchor add 3 10.10.10.10 command, but the command is failing. Which two conditions must be met to be able to enter this command? (Choose two.)

- A. The anchor controller IP address must be within the management interface subnet.
- B. The anchor controller must be in the same mobility group.
- C. The WLAN must be enabled.
- D. The mobility group keepalive must be configured.

E. The indicated WLAN ID must be present on the controller.

Answer: AB

New 300-375 exam questions from PassLeader 300-375 dumps! Welcome to download the newest PassLeader 300-375 VCE and PDF dumps: <http://www.passleader.com/300-375.html> (119 Q&As --> 133 Q&As --> 156 Q&As --> 169 Q&As)

P.S. Free 300-375 dumps are available on Google Drive shared by PassLeader:

https://drive.google.com/open?id=0B-ob6L_QjGLpQ2hZQ0c4c2d1QjA